



| Client:  |  |
|----------|--|
| Order #: |  |
| Project: |  |
| Type:    |  |

# PERFORMANCE DATA

#### CRI

75+ (5000K) 80+ (4000K and lower)

#### CCT

3000K, 3500K, 4000K, 5000K

## **Projected Lifetime**

200,000 Hours (L80); 90,000 Hours (L90)

#### **Dimming**

0-10V Dimming Standard, 10% down to 100%

## **Operating Temperature**

-40°C to +45°C Ambient

#### Warranty

5 year Standard 10 year Optional

# **DESCRIPTION**

The Lila luminaire features classic architectural styling that blends beautifully in a wide range of commercial environments and landscape designs. Prismatic refractor lens with upper reflector for smooth symmetrical light distribution. Heavy gauge aluminum construction with durable, weather resistant polyester powder coat finish in a variety of standard and custom colors. Ideal for parks, urban plazas, shopping centers, boardwalks, apartment complexes, hotels and resorts.

## **FEATURES**

- Heavy-gauge die-cast and spun aluminum construction.
- Available with acrylic or polycarbonate prismatic reflector lens.
- Standard distribution pattern is Type V (360° circular).
- 180° internal cutoff shield is available as an option.
- Available in wattages up to 80W
- Three stainless steel allen screws secure the fixture.
- EPA: 1.36ft2 (20-60W)

# ORDERING INFORMATION

| LILA      |                             |        |          |         |                                  |
|-----------|-----------------------------|--------|----------|---------|----------------------------------|
|           | В С                         | D      | E        | F       | G                                |
| FIXTURE S | SERIES                      | с сст  |          | E OPTIO | ONS                              |
| Lila      | Prismatic Outdoor Luminaire | 30     | 3000K    | PC      | Photocell                        |
| WATTAGE   | WATTAGE/LUMENS              |        | 3500K    | WSF     | Wired Single Fuse                |
| 20        | 20W/1600 <sup>1</sup>       | 40     | 4000K    | WDF     | Wired Double Fuse                |
| 30        | 30W/2300 <sup>1</sup>       | 50     | 5000K    | LS      | Light Shield                     |
| 40        | 40W/3000 <sup>1</sup>       | D VOL  | TAGE     | G WARF  | RANTY <sup>2</sup>               |
| 60        | 60W/4500 <sup>1</sup>       | U      | 120-277V | -       | 5 Year Warranty                  |
| 80        | 80W/6000 <sup>1</sup>       | 347    | 347V     | 10      | 10 Year Warranty                 |
|           |                             | 480    | 480V     | 10L     | 10 Year Warranty including labor |
|           |                             | E FINI | SH       |         |                                  |
|           |                             | BZ     | Bronze   |         |                                  |
|           |                             | BL     | Black    |         |                                  |
|           |                             | WH     | White    |         |                                  |
|           |                             | SL     | Silver   |         |                                  |
|           |                             | CU     | Custom   |         |                                  |


<sup>&</sup>lt;sup>1</sup>Delivered Lumens (5000K)



<sup>&</sup>lt;sup>2</sup> 5 Year Warranty is Standard unless specified




# **DIMENSIONS**



|        | Inches |        |  |  |  |
|--------|--------|--------|--|--|--|
|        | Size X | Size X |  |  |  |
| Medium | 24.00  | 22.00  |  |  |  |

# **OTHER TENON SIZES**



| DRETA-3.5-TN3 (PT3.5) | Round External Tenon Adapter to Slip Over 3.5" Diameter Round Pole to 3" Post Top  |
|-----------------------|--|
| DRETA-4-TN3 (PT4)     | Round External Tenon Adapter to Slip Over<br>4" Diameter Round Pole to 3" Post Top |
| DRETA-5-TN3 (PT5)     | Round External Tenon Adapter to Slip Over<br>4" Diameter Round Pole to 3" Post Top |
| DRETA-6-TN3 (PT6)     | Round External Tenon Adapter to Slip Over 4" Diameter Round Pole to 3" Post Top    |

Please note that this is ordered separately