



Client:	
Order #:	
Project:	
Туре:	

DESCRIPTION

Introducing the Sportino series, the latest generation of sports lighting designed to cater to diverse client requirements. This cutting-edge luminaire combines integrated blind radiator and reflector optics technologies, offering unparalleled glare reduction with minimal impact on light output. Perfect for outdoor sports illumination in municipal, school, and semi-professional settings, the Sportino series provides versatile lighting solutions for football, baseball, hockey, basketball, and various other outdoor sports. Elevate your sports lighting experience with this advanced luminaire.

FEATURES

- Sealed die-casting profile for outdoor applications.
- Low profile, 3G vibration rated compact design minimizes wind load requirements.
- Environmental friendly, IP65 waterproof rating.
- · Available in NEMA 4Hx4V distributions.
- Light engines are available in standard 4000K, 5000K and 5700K (70/80/90 CRI) configurations.
- Scalable Lumen Packages from 50,000 to 68,000 Lumens.

- Optics is precisely designed to shape the distribution, maximizing efficiency and application spacing
- Universal 120-277 VAC or 347-480 VAC input voltage
- Standard with 0-10V dimming driver(s)
- Built in surge suppression with max.20KV @120-277V (Max.40KV @347-480V).
- THD: ≤20%
- Power Factor: ≥90%

PERFORMANCE DATA

CRI

70+

CCT

4000K, 5000K, 5700K

Projected Lifetime

>100,000 Hours (L70)

Dimming

0-10V Dimming Standard, 10% down to 100%

Operating Temperature

-40°C to +55°C Ambient

Warranty

5 year Standard 10 year Optional

ORDERING INFORMATION


SPORTIN	0										
	'	В	С		D	E	F		G		
FIXTURE SERIES				С	C CCT			F MOUNTING			
Sportino	Economy Wraparound				40	4000K		TR	Trunnion		
WATTAGE/LUMENS					50	5000K	G	G WARRANTY ²			
360	360W/51000 ¹				57	5700K		- 5 Year Warranty			
510	510W/68000¹			D	VOLTAGE			10	10 Year Warranty		
					U	120-277V		10L	10 Year Warranty	including labor	
					Н	347-480V					
				E	E FINISH						
					BL	Black					


¹Delivered Lumens (5000K)


² 5 Year Warranty is Standard unless specified



DIMENSIONS







OTHER VIEWS





PHOTOMETRIC DATA

