



Client:	
Order #:	
Project:	
Type:	

DESCRIPTION

This Cielo canopy light has a slim and low profile design which provides a safe and visually appealing lighting experience. Luminaire can be mounted directly or with 3/4" pendant mounting option. Quick mount structure allows for contractors to work safely and easily in the confined space areas. With the patented smart controller, this canopy allows multiple wattages and CCT to choose from. It is the perfect upgrade from a 100W metal halide lamp with the benefit of low maintenance cost.

FEATURES

- LISTING
UL and CUL listed for wet locations
- HOUSING
Solid construction die-cast aluminum body
- FINISH
UV stabilized powder coated finish.
- OPTIONS
Optional photocell
- Finish-Bronze. Color options with adder Build in color adjustable control ranging from 3000K to 5000K
- 0-10V Dimming

PERFORMANCE DATA

CRI

70+

CCT

3000K 4000K, 5000K

Projected Lifetime

190,000 Hours (L70)
58,000 Hours (L90)

Dimming

0-10V Dimming Standard,
10% down to 100%

Operating Temperature

-40°C to +50°C Max Ambient

Warranty

5 year Standard
10 year Optional

ORDERING INFORMATION

CIELO						
	B	C	D	E	F	G

A	FIXTURE SERIES	
	Cielo	Canopy Light
B	WATTAGE/LUMENS	
	42	42W/5451 ¹
	61	61W/7668 ¹
	83	83W/10273 ¹

C	CCT	
	30	3000k
	40	4000K
	50	5000K ²
D	VOLTAGE	
	U	120-277V
E	FINISH	
	WH	White
	BL	Black
	BZ	Bronze
	CU	Custom

F	OPTIONS	
	EM	Emergency Driver ¹
	OS	Occupancy Sensor
	SC	Smart Controller
	PC	Photocell Control
G	WARRANTY³	
	-	5 Year Warranty
	10	10 Year Warranty
	10L	10 Year Warranty including labor

¹ Delivered Lumens (4000K)

² For more information on the Motion Sensor features and benefits see Page 2

³ 5 Year Warranty is Standard unless specified

DIMENSION:

