

Client:	
Order #:	
Project:	
Type:	

DESCRIPTION

The compact dimensions of the RNSS make it a perfect fit for architecture applications with size restrictions. The RNSS Series serves as an ideal lighting solution for a range of settings, including commercial, industrial, retail, and residential spaces. These fixtures find applications in storage/utility areas, coves, display cases, shops, and various task and general area lighting needs.

FEATURES

- Mounting
- V-Hook ready
 - Surface Mounting

- Applications
- Offices
 - Hallways
 - Multipurpose Rooms
 - Conference Rooms

Ratings

- DLC Listed
- UL 1598 suitable for damp locations
- UL 8750 LED equipment in Lighting Products
- Temperature Rated at(-20°C to +50°C) (-4°F to 122°F)
- The 0-10V Dimming type is continuous
- The product can dim to 10%

PERFORMANCE DATA

CRI

70+

CCT

3500K, 4000K, 5000K

Projected Lifetime

>50,000 Hours (L70)

Dimming

0-10V Dimming Standard,
10% down to 100%

Operating Temperature

-20°C to +50°C Ambient

Warranty

5 year Standard
10 year Optional

ORDERING INFORMATION

RNSS						
-------------	--	--	--	--	--	--

A		B		C		D		E		F		G	
FIXTURE SERIES		RNSS		CCT		35		3500K		OPTIONS		EM	
WATTAGE/LUMENS SIZE 4ft		18		40		4000K		VOLTAGE		MS		Motion Sensor	
		20W/2520 ¹		50		5000K		FINISH		WARRANTY²		-	
		25		25W/3400 ¹		U		120-277V				5 Year Warranty	
		30		30W/3990 ¹		WH		White				10 Year Warranty	
		34		34W/4828 ¹		BL		Black				10L	
		38		38W/5282 ¹		SL		Silver				10 Year Warranty including labor	
		45		45W/5985 ¹		CU		Custom					
		WATTAGE/LUMENS SIZE 8ft											
		38		38W/5320 ¹									
		46		46W/6256 ¹									
		54		54W/7182 ¹									
		65		65W/9230 ¹									
		75		75W/10425 ¹									
		90		90W/11970 ¹									

¹Delivered Lumens (5000K)

² 5 Year Warranty is Standard unless specified

DIMENSIONS

Specifications



RNSS 4FT/8FT

Length: 1202/2392 (47.3"/94.2")

Width: 60(2.4")

Depth: 71.2(2.8")

Weight: 1.70/3.40(kg)



PHOTOMETRIC TEST LIST

Catalog No.	Lumens	Watts	Efficacy	CCT Range
	Rated	Rated	Rated	
	3930	30	131	835-850
	3960	30	132	
	3990	30	133	
	835-850	3350	25	134
		3375	25	135
		3400	25	136
	835-850	2484	18	138
		2502	18	139
2520		18	140	
5895		45	131	835-850
5940	45	132		
5985	45	133		
835-850	5206	38	137	
	5244	38	138	
	5282	38	139	
	4760	34	140	835-850
4794	34	141		
4828	34	142		
835-850	7074	54	131	
	7128	54	132	
	7182	54	133	
	6164	46	134	835-850
	6210	46	135	
	6256	46	136	
	835-850	5244	38	138
		5282	38	139
5320		38	140	
835-850	11790	90	131	
	11880	90	132	
	11970	90	133	
	10275	75	137	835-850
	10350	75	138	
	10425	75	139	
	835-850	9100	65	140
		9165	65	141
		9230	65	142